Monochrome laser multifunction printe

## Accelerate Your Work Efficiency with Automatic Document Feeder

The new M6559 series with ADF gives home and small business user easier and faster copying and scanning experiences.



## **BUSINESS READY**

## **ECONOMICAL PRINTER SERIES**



One Step Driver Installation and Direct Printing



Office Document Direct
Print from Mobile Devices



Support Airprint® Mopria®,Pantum App



20000 Page Monthly Duty Cycle



Processor Speed, Memory



Fast Print and Copy Speeds



WiFi and print from mobile device available for M6559NV

## **KEY SPECIFICATIONS**



PRINTING	
PRINTING	20
Print speed	22ppm (A4) / 23ppm (Letter)
First print out time	Less than 7.8s
Processor	600 MHZ
Memory	128 MB
Duplex mode	Manual
Connectivity	High-speed
Maximum monthly duty cycle <sup>(1)</sup>	20,000 pages
Printer language	GDI
COPYING	
Copy speed	22cpm (A4) / 23cpm (Letter)
First copy out time	FB: Less than 10s; ADF: Less than 12s
Zoom	25% - 400%
Max. copy pages	1 - 99 pages
Additional function	ID copy, Receipt copy, N-up copy, Clone copy
SCANNING	
Scanner type	Flatbed + ADF
Max. scan size	216 x 297mm(Flatbed), 216 x 356mm(ADF)
Color scanning	Yes
Output function	Scan to PC Scan to E-mail, PC, FTP Scan to E-mail, PC, FTP iOS, Android
PAPER HANDLING	
Paper input capacity	150 pages
Paper output capacity	100 pages
ADF Capacity	35 pages
Media types	Plain, Thick, Transparency, Cardstock, Label, Envelope and Thin
Media sizes	A4,A5,A6,JIS B5,ISO B5,B6, Letter, Legal, Executive, Statement, Monarch envelope, DL envelope,C5 envelope,C6 envelope,NO.10 envelope, Japanese Postcard,Folio,O-cio,Big 16k, 32k,16k,Big 32k,ZL,Yougata4, Postcard, Younaga3, Nagagata3, Yougata2
Media weight	60~163g/m²
OTHER	
Operating system compatibility	Microsoft Windows Server2008/Server2012/Server2016/Server2019/XP/Vista/Win7/
Dimensions (WxDxH)	417x305x301mm(16.4"×12.0"×11.8")
Neight (with toner cartridge)	8.5Kg (18.7lb)
Power	110V Model: AC100~127V(±10%); 50Hz/60Hz; 6A 220V Model: AC220~240V(-15%,+10%); 50Hz/60Hz; 3A
Recommended temperature	10-32°C (50°F-90°F)"
lumidity range	20 - 80%
SUPPLIES	